

2025 Cobra Model Specifications (subject to change without notice)

| | CX65 (MSRP \$5,998) | CX50SRX FWE (MSRP \$5,948) | CX50SRX King (MSRP \$4,995) | CX50JR (MSRP \$4,895) | CX5E MICROe (MSRP \$7,348) | CX3E MICROe (MSRP \$6,248) |
|-----------------------------|--|--|--|--|--|--|
| Dry Weight | 117 lbs / 53 kg | 88 lbs / 40 kg | 89 lbs / 40 kg | 81 lbs / 36 kg | 94 lbs / 42.6 kg | 98 lbs / 40.5 kg |
| Engine/Motor | Cobra 65cc 2-stroke with Electronic "FANG" Power Valve | Cobra FWE Venom 50cc 2-stroke | Cobra Venom 50cc 2-stroke | Cobra Venom 50cc 2-stroke | Cobra Liquid Cooled Motor | Cobra Liquid Cooled Motor |
| Bore x Stroke | 44.5mm x 41.7mm | 39mm x 41.7mm | 39mm x 41.7mm | 39mm x 41.7mm | N/A | N/A |
| Induction | Case Reed V-Force® Reed Valve 26mm Mikuni VM carb | Case Reed V-Force® Reed Valve 19mm carb | Case Reed V-Force® Reed Valve 19mm carb | Case Reed V-Force® Reed Valve 14mm carb | N/A | N/A |
| Cooling | Liquid cooled Top-end and Case | Liquid cooled Top-end and Case – Twin Radiator | Liquid cooled Top-end and Case – Twin Radiator | Liquid cooled Top-end & Case | Liquid cooled Motor | Liquid cooled Motor |
| Clutch | Hydraulically actuated | Cobra 5Gx Freewheeling 3-Shoe | Cobra 5Gx Freewheeling 3-Shoe | Cobra 5Gx Freewheeling 3-Shoe | N/A | N/A |
| Controls | Pro-Taper Schoolboy Bars (7/8") Breakaway Forged Levers | Micro Bars (5/8") Breakaway Forged Lever |
| Transmission | Six-speed sequential | Single-speed auto | Single-speed auto | Single-speed auto | N/A | N/A |
| Exhaust | Tuned pipe & silencer | Works-style tuned pipe & silencer | Tuned pipe & silencer | Tuned pipe & silencer | N/A | N/A |
| Lubrication | 32:1 – VP Racing X2 1050 | 32:1 - VP Racing X2 1050 | 32:1 – VP Racing X2 1050 | 32:1 - VP Racing X2 1050 | Motor VENOM | Motor VENOM |
| Capacity (gas / battery) | 0.75 Gallons / 2.8 L | 0.75 Gallons / 2.8 L | 0.75 Gallons / 2.8 L | .70 Gallons / 2.6 L | 1.0kW-hr Cool Pack battery | 1.0kW-hr Cool Pack battery |
| Frame | Hybrid Twin Spar | Hybrid Twin Spar | Hybrid Twin Spar | Hybrid Twin Spar | Hybrid Twin Spar | Hybrid Twin Spar |
| Wheelbase | 1130mm | 1038mm | 1038mm | 908mm | 1038mm | 908mm |
| Seat Height | 762mm | 680mm | 680mm | 607mm | 680mm | 607mm |
| Ground Clearance | 250mm | 245mm | 245mm | 216mm | 245mm | 216mm |
| Front Brakes | CARD Hydraulic Disk (205mm) | CARD Hydraulic Disk (160mm) |
| Rear Brakes | CARD Hydraulic Disk (165mm) 1 Touch Adjust | CARD Hydraulic Disk (140mm) 1 Touch Adjust | CARD Hydraulic Disk (140mm) 1 Touch Adjust | CARD Hydraulic Disk (140mm) 1 Touch Adjust | CARD Hydraulic Disk (140mm) 1 Touch Adjust | CARD Hydraulic Disk (140mm) 1 Touch Adjust |
| Front Suspension | CARD Smart-Leg 37mm USD Fully Adjustable 224mm travel | CARD Smart-Leg 32mm USD Fully Adjustable 210mm travel | CARD Smart-Leg 32mm USD Fully Adjustable 210mm travel | CARD Smart-Leg 32mm USD Fully Adjustable 170mm travel | CARD Smart-Leg 32mm USD Fully Adjustable 210mm travel | CARD Smart-Leg 32mm USD Fully Adjustable 170mm travel |
| Rear Suspension | CARD Fully Adjustable (High & Low Speed) 270mm travel - VRS | CARD Fully Adjustable (High & Low Speed) 248mm travel | CARD Fully Adjustable (High & Low Speed) 248mm travel | CARD Adjustable Piggyback 170mm travel | CARD Fully Adjustable (High & Low Speed) 248mm travel | CARD Adjustable Piggyback 170mm travel |
| Wheel Front / Rear | 14" spoke / 12" spoke (Al rims, Al hubs, 9ga. spokes) | Cobra 12" Forged & Anodized Cobra 10" Forged & Anodized | Cobra 12" Forged & Anodized Cobra 10" Forged & Anodized | Cobra 10" Forged & Anodized Cobra 10" Forged & Anodized | Cobra 10" Forged & Anodized Cobra 12" Forged & Anodized | Cobra 10" Forged & Anodized Cobra 10" Forged & Anodized |
| Tires Front / Rear | Dunlop 60-100x14 Geomax MX34 Dunlop 80-100x12 Geomax MX34 | Dunlop 2.5x12 Geomax MX34 Dunlop 2.75x10 Geomax MX34 | Dunlop 2.5x12 Geomax MX34 Dunlop 2.75x10 Geomax MX34 | Dunlop 2.5x10 Geomax MX34 Dunlop 2.75x10 Geomax MX34 | Dunlop 2.5x12 Geomax MX34 Dunlop 2.75x10 Geomax MX34 | Dunlop 2.5x10 Geomax MX34 Dunlop 2.75x10 Geomax MX34 |

CHAMPIONS START HERE.



